



**CUSHMAN®**

# HAULER® 800



## **PRACTICALITY MEETS VERSATILITY.**

The Cushman® Hauler® 800 is built to transport people, tools and materials around work sites with ease. Equipped with your choice of a powerful 48V AC electric or 13.5 hp gas drivetrain, and practical features such as an 8.4 cubic-foot cargo bed and 800 lbs. total load capacity, there is enough power and payload to carry you through the day. The Hauler 800 is the “go to” vehicle when versatility and efficiency is a priority.

**LET'S WORK.®**

**13.5 HP**  
**EFI GAS**

**8.4 CU FT**  
**CARGO BED**

**900 LB**  
**TOW CAPACITY**

**48V AC**  
**ELECTRIC**  
**DRIVETRAIN**





# CUSHMAN® HAULER® 800



BED DIVIDERS



USB & 12V OUTLET

OPTIONAL  
TURN SIGNAL

## OPTIONS & ACCESSORIES

- Improved Surface Tires\*
- Brake Lights\*
- Taillights\*
- Fuel/Oil Gauge (gas vehicle only)\*
- On-board Charger (electric vehicle only)\*
- Premium Steering Wheel\*
- 2" Rear Receiver Hitch\*
- LED Headlights with High/Low Beam
- ROPS-Certified Cab
- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- Weather Enclosure
- USB Outlet
- 12-Volt Outlet
- Canopy Storage Net
- Rearview Mirror
- Side body color

\*Included in Commercial Package



**COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY**

	ELECTRIC MODEL	EFI GAS MODEL
<b>BODY &amp; CHASSIS</b>		
FRAME	Welded Steel w/ E-Shield e-coat plus DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO (Front) /Injection Molded PP (Rear)	
STANDARD COLOR	Patriot Blue	
<b>DIMENSIONS</b>		
OVERALL LENGTH	110 in (279.4 cm)	
OVERALL WIDTH	49 in (125 cm)	
OVERALL HEIGHT	47 in (119.4 cm) (No Canopy)   69.5 in (176.5 cm) (w/ Struts & Roof)	
WHEEL BASE	65.5 in (166.4 cm)	
WHEEL TRACK	37 in (94 cm) Front / 38 in (96.5 cm) Rear	
GROUND CLEARANCE	4.3 in (10.9 cm)	
CARGO DECK CAPACITY	8.4 cu ft (0.24 m <sup>3</sup> )	
CARGO DECK DIMENSIONS	44.5 in x 28.5 in x 12 in (113 cm x 72 cm x 30.5 cm)	
CARGO DECK MATERIAL	Roto-Molded Polyethylene	
<b>POWER</b>		
POWER TRAIN	48V AC	4-Cycle, 24.5 ci (401cc)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	4.4 HP (3.3 kW) Continuous	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	48V	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	Six, 8V Deep Cycle	One, 12V Maintenance Free
BATTERY CHARGER	48V DC PowerWise™ QE, 120V AC, UL/CSA	N/A
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replacable Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) tank
SPEED CONTROLLER	235 Amp AC Controller	N/A
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse	Forward - Reverse
REAR AXLE RATIO	16.99: 1	11.47: 1 (Forward) 14.35:1 (Reverse)
<b>PERFORMANCE</b>		
SEATING CAPACITY	2-Person (Bench)	
WEIGHT W/O BATTERIES	735 lb (333.4 kg)	761 lb (345.2 kg)
CURB WEIGHT	1101 lb (499.4 kg)	791 lb (358.8 kg)
VEHICLE LOAD CAPACITY	800 lb (362.9 kg)	
BED LOAD CAPACITY	400 lb (181.4 kg)	
TOWING CAPACITY	900 lb (408.2 kg)	
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)	
SPEED	14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph)	
<b>STEERING &amp; SUSPENSION</b>		
STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	18 x 8.5- 8 (6 Ply-rated)	

[www.cushman.com](http://www.cushman.com)

©2019 Textron Specialized Vehicles Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82288-G7 (Rev. 12/2018)